

AMC Doc. #: AMC1117_B
March 2002





AMC1117

1A Low DROPOUT POSITIVE REGULATOR

DESCRIPTION
The AMC1117 series of positive adjustable and fixed regulators is designed to provide 1A for applications requiring high efficiency. All internal circuitry is designed to operated down to 800mV input to output differential and the dropout voltage is fully specified as a function of load current. The AMC1117 offers current limiting and thermal protection. The on chip trimming adjusts the reference voltage accuracy to 1%.

FEATURES
■ Output current of 1A typical ■ Three-terminal adjustable or fixed 1.8V, 2.5V, 2.85V, 3.3V, 5.0V outputs ■ Low dropout of typical 800mV ■ Thermal protection built in ■ Typical 0.015% line regulation ■ Typical 0.01% load regulation □ Fast transient response □ Available in SOT-223 and TO-252 packages □ Pin assignment identical to earlier LT1117 series

APPLICATIONS	
■	2.85V Model for SCSI-2 Active Termination
■	Battery Charger
■	High Efficiency Linear Regulators
■	Battery Powered Instrumentation
■	Post Regulator for Switching DC/DC Converter
♦	Voltage Options
AMC1117-1.8	– 1.8V Fixed
AMC1117-2.5	– 2.5V Fixed
AMC1117-2.85	– 2.85V Fixed
AMC1117-3.3	– 3.3V Fixed
AMC1117-5.0	– 5.0V Fixed
AMC1117	– Adjustable Output


PACKAGE PIN OUT
 3-Pin Plastic SOT-223 Surface Mount (Top View)
 3-Pin Plastic TO-252 Surface Mount (Top View)

ORDER INFORMATION				
T _A (°C)	SK	SOT223	SJ	TO-252
		3-pin		3-pin
0 to 70	AMC1117-X.XSK		AMC1117-X.XSJ	
	AMC1117SK		AMC1117SJ	
Note: All surface-mount packages are available in Tape & Reel. Append the letter “T” to part number (i.e. AMC1117-X.XSJT).				

AMC1117

1A LOW DROPOUT POSITIVE REGULATOR

BLOCK DIAGRAM



AMC1117

1A LOW DROPOUT POSITIVE REGULATOR

ABSOLUTE MAXIMUM RATINGS (Note 1)	
Input Voltage	13V
Operating Junction Temperature Range, T_J	0°C to 150°C
Storage Temperature Range	-65°C to 150°C
Lead Temperature (soldering, 10 seconds)	260°C
Note 1: Exceeding these ratings could cause damage to the device. All voltages are with respect to Ground. Currents are positive into, negative out of the specified terminal.	

POWER DISSIPATION TABLE					
Package	θ_{JA} (°C/W)	Derating factor (mW/°C) $T_A \geq 25^\circ\text{C}$	$T_A \leq 25^\circ\text{C}$ Power rating(mW)	$T_A = 70^\circ\text{C}$ Power rating(mW)	$T_A = 85^\circ\text{C}$ Power rating (mW)
SK	136	7.35	919	588	478
SJ	80	12.5	1562	1000	812
Note : 1. θ_{JA} : Thermal Resistance-Junction to Ambient, D_F : Derating factor, P_o : Power consumption. Junction Temperature Calculation: $T_J = T_A + (P_D \times \theta_{JA})$, $P_o = D_F \times (T_J - T_A)$ The θ_{JA} numbers are guidelines for the thermal performance of the device/PC-board system. All of the above assume no ambient airflow. 2. θ_{JT} : Thermal Resistance-Junction to Ambient, T_C : case(Tab) temperature, $T_J = T_C + (P_D \times \theta_{JT})$ For SK package, $\theta_{JT} = 15.0^\circ\text{C/W}$. For SJ package, $\theta_{JT} = 7.0^\circ\text{C/W}$.					

RECOMMENDED OPERATING CONDITIONS					
Parameter	Symbol	Recommended Operating Conditions			Units
		Min.	Typ.	Max.	
Input Voltage	V_{IN}	2.7		12	V
Load Current (with adequate heatsinking)	I_o	5			mA
Input Capacitor (V_{IN} to GND)		1.0			μF
Output Capacitor with ESR of 10 Ω max., (V_{OUT} to GND)		4.7			μF
Junction temperature	T_J			125	°C

AMC1117

1A LOW DROPOUT POSITIVE REGULATOR

ELECTRICAL CHARACTERISTICS							
Unless otherwise specified, V _{IN} = V _{OUT} +2V, I _O =10mA, and T _J = 25°C.							
Parameter		Symbol	Test Conditions	AMC1117			Units
				Min	Typ	Max	
Reference Voltage	AMC1117	V _{REF}	I _O = 10mA, V _{IN} – V _{OUT} = 2V	1.238	1.250	1.262	V
			10mA ≤ I _O ≤ 1A, V _{OUT} +1.5V ≤ V _{IN} ≤ 12V	1.230	1.250	1.270	
Output Voltage	AMC1117-1.8	V _{OUT}	I _O = 10mA, V _{IN} = 3.8V	1.782	1.8	1.818	V
			10mA ≤ I _O ≤ 1A, 3.2V ≤ V _{IN} ≤ 12V	1.764	1.8	1.836	
	AMC1117-2.5		I _O = 10mA, V _{IN} = 4.5V	2.475	2.500	2.525	
			10mA ≤ I _O ≤ 1A, 4.25V ≤ V _{IN} ≤ 12V	2.450	2.500	2.550	
	AMC1117-2.85		I _O = 10mA, V _{IN} = 4.85V	2.821	2.850	2.879	
			10mA ≤ I _O ≤ 1A, 4.25V ≤ V _{IN} ≤ 12V	2.805	2.850	2.895	
	AMC1117-3.3		I _O = 10mA, V _{IN} = 5.0V	3.267	3.300	3.333	
			10mA ≤ I _O ≤ 1A, 4.75V ≤ V _{IN} ≤ 12V	3.235	3.300	3.365	
	AMC1117-5.0		I _O = 10mA, V _{IN} = 7.0V	4.950	5.000	5.050	
			10mA ≤ I _O ≤ 1A, 6.5V ≤ V _{IN} ≤ 12V	4.900	5.000	5.100	
Line Regulation	AMC1117	ΔV _{OI}	I _O = 10mA, V _{OUT} +1.5V ≤ V _{IN} ≤ 12V		0.04	0.20	%
	AMC1117-X.X		I _O = 10mA, V _{OUT} +1.5V ≤ V _{IN} ≤ 12V		1.0	6.0	mV
Load Regulation	AMC1117	ΔV _{OL}	10mA ≤ I _O ≤ 1A, V _{IN} – V _{OUT} = 3V		0.10	0.40	%
	AMC1117-X.X		10mA ≤ I _O ≤ 1A, V _{IN} = V _{OUT} +1.5V		1.0	10.0	mV
Dropout Voltage		ΔV	I _O = 10mA		0.8	1.15	V
			I _O = 1A		0.8	1.30	
Minimum Load Current (Note 1)			V _{IN} ≤ 12V		1.7	5	mA
Quiescent Current	AMC1117-X.X	I _Q	V _{IN} ≤ 12V		6	10	mA
Current Limit		I _{CL}	V _{IN} – V _{OUT} = 3V	1	1.2		A
Adjust Pin Current			I _O = 10mA, V _{IN} – V _{OUT} = 2V		50	120	μA
Thermal Regulation (Note 2)			T _A = 25°C, 30 ms pulse		0.01	0.1	%/W
Ripple rejection (Note 2)		R _R	f _O = 120Hz, 1V _{RMS} , I _O = 400mA, V _{IN} – V _{OUT} = 3V	60	75		dB


Note 1: For the adjustable device, the minimum load current is the minimum current required to maintain regulation. Normally the current in the resistor divider used to set the output voltage is selected to meet the minimum load current requirement.

Note 2: These parameters, although guaranteed, are not tested in production.


Characterization Curves

Unless otherwise specified, $V_{IN} = V_{OUT} + 2V$, $C_{IN} = 1\mu F$, $C_{OUT} = 4.7\mu F$, $T_A = 25^\circ C$


Load Regulation




Load Regulation




Load Regulation




Load Regulation




Temperature Stability



Quiescent Current vs. Temperature




APPLICATION INFORMATION




Adjustable Regulator

$$V_{OUT} = 1.25V \left(1 + \frac{R2}{R1} \right)$$



5V Regulator with Shutdown



Fixed Voltage Regulator

Application Note:

Maximum Power Calculation:

$$P_{D(MAX)} = \frac{T_{J(MAX)} - T_{A(MAX)}}{\theta_{JA}}$$

$T_J(^{\circ}C)$: Maximum recommended junction temperature

$T_A(^{\circ}C)$: Ambient temperature of the application

$\theta_{JA}(^{\circ}C/W)$: Junction-to-junction temperature thermal resistance of the package, and other heat dissipating materials.

The maximum power dissipation of a single-output regulator :

$$P_{D(MAX)} = [(V_{IN(MAX)} - V_{OUT(NOM)}) \times I_{OUT(NOM)} + V_{IN(MAX)} \times I_Q]$$

Where: $V_{OUT(NOM)}$ = the nominal output voltage

$I_{OUT(NOM)}$ = the nominal output current, and

I_Q = the quiescent current the regulator consumes at $I_{OUT(MAX)}$

$V_{IN(MAX)}$ = the maximum input voltage

Then $\theta_{JA} = (150^{\circ}C - T_A)/P_D$

Thermal consideration:

When power consumption is over about 404 mW (for SOT-223 package, 687mW for TO-252 package, at $T_A=70^{\circ}C$), additional heat sink is required to control the junction temperature below $125^{\circ}C$.

The junction temperature is: $T_J = P_D (\theta_{JT} + \theta_{CS} + \theta_{SA}) + T_A$

$P_D \equiv$ Dissipated power.

$\theta_{JT} \equiv$ Thermal resistance from the junction to the mounting tab of the package.


$\theta_{CS} \equiv$ Thermal resistance through the interface between the IC and the surface on which it is mounted.
(typically, $\theta_{CS} < 1.0^{\circ}C/W$)

$\theta_{SA} \equiv$ Thermal resistance from the mounting surface to ambient (thermal resistance of the heat sink).

If PC Board copper is going to be used as a heat sink, below table can be used to determine the appropriate size of copper foil required. For multi-layered PCB, these layers can also be used as a heat sink. They can be connected with several through hole vias.


PCB $\theta_{SA} (^{\circ}C/W)$	59	45	38	33	27	24	21
PCB heat sink size (mm ²)	500	1000	1500	2000	3000	4000	5000

Recommended figure of PCB area used as a heat sink.




AMC1117
1A LOW DROPOUT
POSITIVE REGULATOR

3-Pin Surface Mount SOT-223 (SK)



3-Pin Surface Mount TO-252 (SJ)



IMPORTANT NOTICE

ADD Microtech (ADDM) reserves the right to make changes to its products or to discontinue any integrated circuit product or service without notice, and advises its customers to obtain the latest version of relevant information to verify, before placing orders, that the information being relied on is current.

A few applications using integrated circuit products may involve potential risks of death, personal injury, or severe property or environmental damage. ADDM integrated circuit products are not designed, intended, authorized, or warranted to be suitable for use in life-support applications, devices or systems or other critical applications. Use of ADDM products in such applications is understood to be fully at the risk of the customer. In order to minimize risks associated with the customer's applications, the customer should provide adequate design and operating safeguards.

ADDM assumes no liability to customer product design or application support. ADDM warrants the performance of its products to the specifications applicable at the time of sale.

U.S.

ADD Microtech Inc.

492 Altamont Drive
Milpitas, CA 95035

TEL: (408) 9410420

FAX: (408) 9410864

Asia Pacific region

ADD Microtech Corp

3F, 132, Sec. 4, Chung Hsiao E. Rd.,
Taipei, Taiwan

TEL: 2-27760166

FAX: 2-27764208
