


注：“*”為重點尺寸



底座向上示意圖

PCB Labyout recommended

SPECIFICATIONS *NON SHORTING
 Function :2P2T Rating : 0.1A 30V DC
 Contact Resistance : 100mΩ Max 100毫歐以下
 Insulation Resistance : 100MΩ Min 100兆歐以上
 Operating Force :200gf±50gf
 Life Test :10.000 Cycles 15~18 Cycles/Min

7	CAM STICK	SUS	1	NATERAL	SCALE (比例): 1: 1	TOLERANCE ARE ±0.30 10~30 ± 0.20 5~10 ± 0.15 ~5 ± 0.10	TITLE		SIZE	A4	
6	SPRING	SWC	1	NATERAL			圖名				PUSH SWITCH
5	CONTACT CLIP	PBS C5210R-EH	2	Ag CLAD			DWG NO.		BPSJ-2215L		UNIT
4	COVER	POM	1	WHITE			圖號		日期		mm
3	KNOB	POM	1	BLUE			REV.	A	2012-01-02		SHEET
2	TERMINAL	BRASS STRIP	6	Ag PLATED OVER NI PLATED			版本				張數
1	CASE	PBT	1	BLACK	CHECKED BY		DRAWN BY		1 of 1		
NO	PART NAME	MATERIALS	Q'TY	FINISHING	FILE NAME :BPSJ-2215L		審核		製圖		