



SPECIFICATION

CONTACT RATING :5A250VAC 10A125VAC (VDE RJ)
 10A 250V/125V(S RJ)
 6(1)A250V ~ uT85/55(D N S FI)
 5A/2X250V ~ (COC)

INITIAL CONTACT RESISTANCE:50Milliohms Max.
 INSULATION RESISTANCE :500 Megohms Min 500VDC.
 WITHSTAND VOLTAGE :1,000 VAC-1 Minute.
 LIFE EXPECTANCY :10,000 Cycles.
 OPERATING FORCE :400±200gf.

MODEL NO	SCHEMATIC
BR-11C-11L-C	

Safety Certificate	FILE NO:
RJ	E105856
S	LR112904-6
N	40004251
FI	CQC03002004731

Safety Certificate	FILE NO:
D	116036
S	9432010
N	P05203712
FI	21533

主要尺寸 (*)		重要尺寸	
A1	$\phi 23 \pm 0.15$	A	7.9 ± 0.1
		B	7.08 ± 0.1

大廣有限公司 DA KOANG CO., LTD.				DES	BR SERIES		
TOL	>0.3~6	±0.1	DRW	F. J. R	05/03/03	TITLE	ROCKER SWITCH
	>6~30	± 0.15	DESIGN	F. J. R	05/03/03	DWG NO.	PNA-000164
	>30	±0.3	CHECKED			MODEL	5171
SCALE	1.5:1	UNIT	mm	APPROVED		VERSION	A1
PROJ		TOTAL	1	PAGE	1	DATE	