



SPECIFICATION

CONTACT RATING :5A250VAC 10A125VAC (VDE RU)
 10A 250V/125V (CS RU)
 6(1)A250V ~ uT85/55 (D N S F)
 5A/2X250V ~ (CCC)

INITIAL CONTACT RESISTANCE:50Milliohms Max.
 INSULATION RESISTANCE :500 Megohms Min 500VDC.
 WITHSTAND VOLTAGE :1,000 VAC-1 Minute.
 LIFE EXPECTANCY :10,000 Cycles.
 OPERATING FORCE :400 \pm 200 gf.

MODEL NO	SCHEMATIC
BR-13E-11L-C	

Safety Certificate	FILE NO:
RU	E105856
CS	LR112904-6
D	40004251
CCC	CQC03002004731

Safety Certificate	FILE NO:
D	116036
S	9432010
N	P94100673
F	175590-01

主要尺寸 (*)		重要尺寸	
A1	$\varnothing 23 \pm 0.15$	A	7.9 ± 0.1
		B	7.08 ± 0.1

PRONIC ELECTRONICS (SHENZHEN) CO., LTD				DES	BR SERIES		
TOL	>0.3~6	± 0.1	DRW	F. J. R04/11/27	TITLE	ROCKER SWITCH	
	>6~30	± 0.15	DESIGN	F. J. R04/11/27	DWG NO.	PNA-000099	
	>30	± 0.3	CHECKED		MODEL	5172	
	ANG	$\pm 1^\circ$	APPROVED		VERSION	A1	
SCALE	1.5:1	UNIT	mm	TOTAL	1	PAGE	1
PROJ						DATE	