




SPECIFICATION

ELECTRICAL

- Contact Current Rating : 1 Ampere
- Contact Resistance : 25 mΩ Max
- Insulator Resistance : 1,000 MΩ Min
- Dielectric Withstanding Voltage : 1000 V AC RMS 60 Seconds

MATERIAL

- Insulator : PBT UL 94V-0
- Contact : Brass
- Contact Plated : Selective Gold Over Copper Plated
- Shell : Steel
- Shell Plated : Tin , Nickel OR Zinc Plated

MECHANICAL

- Mating cycles : 3000 Cycles Min.

Operation Temperature : - 40℃ to + 105℃

HDSSXXSB1#1	DIMENSIONS			
CONTACTS	A	B	C	D
15	16.33	24.99	30.81	2.29
26	24.66	33.32	39.25	2.29
44	38.38	47.04	53.04	2.29
62	54.84	63.50	69.50	2.41

UNIT: mm

CENTRONIC PRECISION ELECTRONIC COMPANY

三川精密電子有限公司

TEL:886-2-2686-8788 FAX:886-2-2686-0018

E-MAIL:Centron@tpts6.seed.net.tw

MORLINKOM TECHNOLOGY LTD

魔林科技有限公司

E-MAIL:Cen8888@gmail.com

繪圖 DRAWN BY
FUFU

核對 CHECKED BY
WENDY

日期 DATE
2011/03/30

比例 SCALE
1:1

HDSSXXSB1#1

圖號 501-XX

DRAWING NO.