



**SPECIFICATION**  
**CONTACT RATING:** 10A 250VAC  
**INSULATION RESISTANCE:** 500V DC for 1 min.  
**Dielectric strength:** 2000V a.c. for 1 min.  
**Withstand voltage:** AC 500V 60Hz 1 minute

Cd < 100ppm  
 Cr+6 < 1000ppm  
 Hg < 1000ppm  
 Pb < 1,000ppm  
 銅合金 Pb < 40,000ppm  
 PBB < 1000ppm  
 PBDE < 1000ppm

TOLERANCES	
0.5MM-5MM	±0.2MM
5MM-30MM	±0.4MM
30MM-120MM	±0.6MM
120MM-315MM	±1.0MM
315MM-1000MM	±1.6MM
1000MM-2000MM	±2.4MM

NO	DESCRIPTION	MATERIAL	QTY	SGS REPORT NO.
1	PIN	BRONZE, NICKEL (銅合金)	2	CE/2005/B2486
2	HOUSING	BAKELITE BLACK	1	CE/2004/C2264
3	GROUND	BAKELITE, BLACK	1	CE/2004/C2264
4	CONTACT	BRONZE, NICKEL	2	KA/2004/80319/A-1

General Tolerance	繪圖 Draw By	設計 Designed By	比例尺 Scale
	C.T WANG	C.T WANG	1:1
版本 Version	核準 Approved By	核準日期 Date	單位 UNIT
2	C.C HUANG	17 NOV 2005	m/m

4mm AC ADAPTR EUROPEAN 220V TO 110V 125V15A BAKELITE BLACK		REF. NO.