



SPECIFICATION
 CONTACT RATING: 10A 250VAC
 INSULATION RESISTANCE: 500V DC for 1 min.
 Dielectric strength: 2000V a.c. for 1 min.
 Withstand voltage: AC 500V 60Hz 1 minute

Cd < 100ppm
 Cr+6 < 1000ppm
 Hg < 1000ppm
 Pb < 1,000ppm
 銅合金 Pb < 40,000ppm
 PBB < 1000ppm
 PBDE < 1000ppm

TOLERANCES
0.5MM-5MM=±0.2MM
5MM-30MM=±0.4MM
30MM-120MM=±0.6MM
120MM-315MM=±1.0MM
315MM-1000MM=±1.6MM
1000MM-2000MM=±2.4MM

NO	DESCRIPTION	MATERIAL	QTY	SGS REPORT NO.
1	PIN	BRONZE, NICKEL(銅合金)	2	CE/2005/B2486
2	HOUSING	BAKELITE BLACK	1	CE/2004/C2264
3	GROUND	BAKELITE, BLACK	1	CE/2004/C2264
4	CONTACT	BRONZE, NICKEL	2	KA/2004/80319/A-1

General Tolerance	繪圖 Draw By C.T WANG	設計 Designed By C.T WANG	比例尺 Scale 1:1
版本 Version 2	核準 Approved By C.C HUANG	核準日期 Date 17 NOV 2005	單位 UNIT m/m

大廣有限公司
 DA KOANG CO., LTD.

1117
 4mm AC ADAPTR
 EUROPEAN 220V TO 110V
 125V15A BAKELITE BLACK

REF.NO.